

# WATERBATH

axyos

## w20

**Capacity (litre) filled** 20

**Exterior [Stainless Steel Facia]** 778 x 350 x 233  
(long x wide x deep mm)

**Interior [Stainless Steel]** 503 x 298 x 160  
(long x wide x deep mm)  
Rounded edges sterility  
& ease of cleaning

**Heating** 1.0kW  
(stainless sheathed element)

**Micro-Digital control** Included  
(with digital readout and lcd)

**Temperature Range** Ambient +5°C to 80°C  
(other ranges available)

**Temperature Accuracy** ±0.1°C at sensor. Bath typically ± 0.2°C

**Electrical** 220-240v 50-60Hz single phase  
(alternative power ranges available)

**User Calibration facility** Included

**Tamper proof control** Included



### Options Description

<b>at</b>	°C alarm - Audible & visual for ±°C tolerances
<b>cr</b>	Circular 7 day or 24 hr chart recorder for °C (pls call for other parameters/types)
<b>cn</b>	Circulation pump for increased spatial accuracy & °C response
<b>x</b>	Circulation from bath to external device and returned (Std rating 12lpm - 2.07m head pressure)
<b>cl</b>	Constant level device replacing evaporation
<b>pc</b>	Programmable control system
<b>rc</b>	Programmable ramp controller (cannot be installed if p selected)
<b>l</b>	Removable gabled lid to suit bath
<b>r</b>	°C control from +5 to 80°C (add circulation also)
<b>tc</b>	Countdown to stop timer (not required if any p option selected)
<b>to</b>	Auto programmable start stop timer (not required if any p option selected)
<b>dt</b>	Tap to allow bath to be drained

